



**UL1007**

**300V**



General purpose wire for internal wiring of electronic and electrical equipment and household appliances.

UL1007 Appliance Hookup Wire 300V					
Part Number	Gauge (AWG)	Stranding	Outside Diameter	Colors	Spool/FT
CKW1007-28PVC	28	7x 36	.047	0-5	1000
CKW1007-26PVC	26	7 x 34	.051	0-5	1000
CKW1007-24PVC	24	7 x 32	.056	0-5	1000
CKW1007-22PVC	22	7 x 30	.063	0-5	1000
CKW1007-20PVC	20	10 x 30	.071	0-5	1000
CKW1007-18PVC	18	16 x 30	.077	0-5	500
CKW1007-16PVC	16	26 x 30	.090	0-5	500
CKW1007-14PVC	14	41 x 30	.103	0-5	500
CKW-1007-12PVC	12	65 x 30	.121	0-5	<b>250</b>



**Product Construction:**

**Conductor:**

28-12AWG  
Fully annealed tinned copper (ASTM-B)  
Solid or stranded conductor

**Insulation:**

UL grade PVC/RoHS certified  
Colors: 0/BLK, 1/BRN, 2/RED, 3/ORG, 4/YEL, 5/GRN  
Temperature Range: -10°C-105°C  
Dielectric Strength: 300V/Mil  
Flammability: VW-1

**Compliances:**

UL Style 1007/1569-105°C, 300V  
CSA Type TEW  
RoHs Compliant  
Meets UL VW-1 Vertical Wire Flame Test

