



Internal wiring for various types of electronic, and electrical equipment including consumer electronics, household appliances, panels, meters and point to point wiring.

### UL1015 Electronics Hookup Wire 600V

Part Number	Gauge (AWG)	Stranding	Outside Diameter	Colors	Spool/FT
CKW1015-24PVC	24	7 x 32	.088	0-5	1000
CKW1015-22PVC	22	7 x 30	.093	0-5	1000
CKW1015-20PVC	20	10 x 30	.100	0-5	1000
CKW1015-18PVC	18	16 X 30	.110	0-5	500
CKW1015-16PVC	16	26 X 30	.123	0-5	500
CKW1015-14PVC	14	41 X 30	.138	0-5	500
CKW1015-12PVC	12	65 X 30	.158	0-5	250
CKW1015-10PVC	10	105 X 30	.180	0-5	250
CKW1028-8PVC	8	133 x 29	.262	0-5	100
CKW1283-6PVC	6	133 x 27	.332	0-5	100

#### Product Construction:

##### Conductor:

24-10AWG  
Fully annealed tinned copper (ASTM B-33)  
Solid or stranded conductor

##### Insulation:

UL grade PVC/RoHs certified  
Colors: 0/BLK, 1/BRN, 2/RED, 3/ORG, 4/YEL, 5/GRN  
Temperature Range: -10°C-105°C  
Dielectric Strength: 600V/Mil  
Flammability: VW-1

##### Compliances:

UL Style 1015-105°C, 600V  
CSA Type TEW  
RoHs Compliant  
Meets UL VW-1 Vertical Wire Flame Test



ISO9001