



H03VVH2-F
H03VV-F
300V/300V

Internal hook-up cable 300V

Internal hook-up cable for small appliances and consumer electronics.

Construction No. of cores × nominal cross section mm ²	Conductor construction		Insulation		Cable	
	OD single-wire max. mm	OD conductor nom. mm	Wall thickness nom. mm	OD of core nom. mm	Wall thickness of Jacket nom. mm	Overall Diameter Cable nom. mm
H03VVH2-F						
2×0.5	0.21	0.9	0.5	1.9	0.6	3.2×5.2
2×0.75	0.21	1.1	0.5	2.1	0.6	3.4×5.6
H03VV-F						
2×0.5	0.21	0.9	0.5	1.9	0.6	5.1
2×0.75	0.21	1.1	0.5	2.1	0.6	5.5
3G0.5	0.21	0.9	0.5	1.9	0.6	5.4
3G0.75	0.21	1.1	0.5	2.1	0.6	5.9
4G0.5	0.21	0.9	0.5	1.9	0.6	6.0
4G0.75	0.21	1.1	0.5	2.1	0.6	6.5

Product Construction:

Conductor:

Fine stranded copper (bare or tinned)

Specification:

Multicore constructions: 2-4 cores

TI2 PVC (conductor)

TMW PVC Sheath or SR-PVC/RoHs certified

Temperature Range: -20°C to 80°C

Nominal Voltage 300/300V

Compliances:

DIN VDE-0295

RoHs Compliant

IEC 52

IEC 53

VDE

CE/109851



ISO9001

